Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	19800284	
Valid tyre size	7.50 - 16	
LI / SI / PR	98 A6 / 90 A8, 6 PR	
TL/TT	тт	
Brand	MRL	
Tread pattern	MTF 222	



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19800284
EAN	8907375037476
Valid tyre size	7.50 - 16
LI / SI / PR	98 A6 / 90 A8, 6 PR
TL/TT	ТТ
Brand	MRL
Tread pattern	MTF 222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17,40
Recommended rim size	5.5F
Maximum air pressure [bar].	2,80
Section width (mm)	205
Outer diameter of tyre [mm].	820
Stat. radius (SLR) [mm]	370
Rolling circumference [mm].	2445
Tread depth (mm)	21,0
Tyre capacity 75% [ltr.]	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
98 A6	750	30		2,80	
90 A8	600	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.