

TYRES

Product group	Tyres
Item number	19800288
Valid tyre size	6.50 - 20
LI / SI / PR	102 A6 / 95 A8, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 221



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- It is also suitable for ploughing and transport applications.
- Its typical tread pattern provides very good steering control in the field.

Technical Informations

Item number	19800288
EAN	8907375034772
Valid tyre size	6.50 - 20
LI / SI / PR	102 A6 / 95 A8, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 221
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	16,30
Recommended rim size	5.00F
Permitted rim size	4.00E, 5.50F
Maximum air pressure [bar].	4,50
Section width (mm)	180
Outer diameter of tyre [mm].	864
Stat. radius (SLR) [mm]	406
Rolling circumference [mm].	2565
Tread depth (mm)	18,0
Tyre capacity 75% [ltr.]	33
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 A6	850	30		4,50	
95 A8	690	40		4,50	