# Bohnenkamp Moving Professionals

20.09.2024

### TYRES

Product group	Tyres
Item number	19800289
Valid tyre size	31 x 15.5 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MTR 600



#### Notes and features

- The MRL MTR 600 is a tyre for smaller tractors and agricultural trailers.
- Its flat, agricultural tread pattern and large contact area provide high traction on dry and wet surfaces.
- The tyre is also very suitable for tillage implements, trenchers and lawn maintenance applications.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	19800289
EAN	8907375025596
Valid tyre size	31 x 15.5 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MTR 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,75
Recommended rim size	13LB
Maximum air pressure [bar].	5,20
Section width (mm)	360
Outer diameter of tyre [mm].	790
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2300
Number of lugs	19x2
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 B	1600	50		5,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.