

TYRES

Product group	Tyres
Item number	19800293
Valid tyre size	7.50 - 20
LI / SI / PR	109 A6 / 101 A8, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 212



Notes and features

- The MRL MTF 212 is a front tractor tyre.
- Its 3-rib tread pattern ensures good grip in the ground and good steering control.
- The circumferential reinforced ribs keep the tyre on track and prevent it from slipping sideways.
- Strong casing plies and a cut- and crack-resistant rubber compound guarantee a long service life for the tyre.

Technical Informations

Item number	19800293
EAN	8907375039579
Valid tyre size	7.50 - 20
LI / SI / PR	109 A6 / 101 A8, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 212
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	19,25
Recommended rim size	5.5F
Permitted rim size	5.00F
Maximum air pressure [bar].	3,40
Section width (mm)	205
Outer diameter of tyre [mm].	915
Stat. radius (SLR) [mm]	431
Rolling circumference [mm].	2725
Tread depth (mm)	20,0
Tyre capacity 75% [ltr.]	45
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A6	1030	30		3,40	
101 A8	825	40		3,40	