

TYRES

Product group	Tyres	
Item number	19800295	
Valid tyre size	23 x 10.50 - 12	
LI / SI / PR	107 A3, 8 PR	
TL/TT	TL	
Brand	MRL	
Tread pattern	MTR 600	



Notes and features

- The MRL MTR 600 is a tyre for smaller tractors and agricultural trailers.
- Its flat, agricultural tread pattern and large contact area provide high traction on dry and wet surfaces.
- The tyre is also very suitable for tillage implements, trenchers and lawn maintenance applications.



Technical Informations

Item number	19800295
EAN	8907375047338
Valid tyre size	23 x 10.50 - 12
LI / SI / PR	107 A3, 8 PR
	TL
TL/TT	
Brand	MRL
Tread pattern	MTR 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,00
Recommended rim size	8.1/2JA
Permitted rim size	7JA
Maximum air pressure [bar].	3,00
Section width (mm)	255
Outer diameter of tyre [mm].	590
Stat. radius (SLR) [mm]	260
Rolling circumference [mm].	1682
Tread depth (mm)	15,0
Number of lugs	15x2
Tyre capacity 75% [ltr.]	28
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 A3	975	15		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.