

TYRES

Product group	Tyres
Item number	19800296
Valid tyre size	5.00 - 12
LI / SI / PR	70 A6, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTR 302



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The MRL MTR 302 is a bias tyre for small tractors.
- The tractor tread pattern with high lugs provides high traction and good self-cleaning.
- The tyre is ideally suitable for soil tillage implements on muddy ground.

Technical Informations

Item number	19800296
EAN	8907375053254
Valid tyre size	5.00 - 12
LI / SI / PR	70 A6, 8 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTR 302
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,70
Recommended rim size	3.00D DT
Permitted rim size	3.00D, 4JA
Maximum air pressure [bar].	3,40
Section width (mm)	128
Outer diameter of tyre [mm].	528
Stat. radius (SLR) [mm]	245
Rolling circumference [mm].	1560
Tread depth (mm)	19,5
Number of lugs	12x2
Tyre capacity 75% [ltr.]	8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
70 A6	335	30		3,40	