

TYRES

Product group	Tyres	
Item number	19800429	
Valid tyre size	13 x 5.00 - 6	
LI/SI/PR	6 PR	
TL/TT	TL	
Brand	Kings Tire	
Tread pattern	KT-302	



Notes and features

• Dear trading partner, this item is not part of our main programme. For this reason, we can only publish limited technical information in the online shop.

- For further information, please do not hesitate to contact us by telephone
- Agricultural machinery business: +49 541 12163-100
- Tyre business: +49 541 12163-200



Technical Informations

Item number	19800429
EAN	5707562368399
Valid tyre size	13 x 5.00 - 6
LI / SI / PR	6 PR
TL/TT	TL
Brand	Kings Tire
Tread pattern	KT-302
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1,75
Recommended rim size	3.50
Maximum air pressure [bar].	4,10
Section width (mm)	126
Outer diameter of tyre [mm].	327
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	255			4,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.