

TYRES

| Product group | Tyres | |
|-----------------|----------------------|--|
| Item number | 19800433 | |
| Valid tyre size | 23 x 10.50 - 12 | |
| LI / SI / PR | 94 A8 / 107 A8, 8 PR | |
| TL/TT | TL | |
| Brand | Starco | |
| Tread pattern | AS Loader | |



Notes and features

- The AS Loader was specially developed for skid steer loaders and compact tractors.
- Its tractor pattern provides high traction and excellent selfcleaning properties.
- The tyre performs excellently, even on soft and muddy surfaces.



Technical Informations

| Item number | 19800433 |
|------------------------------|----------------------|
| EAN | 5707562380216 |
| Valid tyre size | 23 x 10.50 - 12 |
| LI / SI / PR | 94 A8 / 107 A8, 8 PR |
| TL/TT | TL |
| Brand | Starco |
| Tread pattern | AS Loader |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 10,50 |
| Recommended rim size | 8.50 |
| Permitted rim size | 7.00 |
| Maximum air pressure [bar]. | 2,50 |
| Section width (mm) | 262 |
| Outer diameter of tyre [mm]. | 580 |
| Stat. radius (SLR) [mm] | 255 |
| Rolling circumference [mm]. | 1737 |
| Tread depth (mm) | 15,4 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 94 A8 | 670 | 40 | Drive Wheel | 2,50 | |
| 107 A8 | 975 | 40 | Free Rolling | 2,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.