

TYRES

Product group	Tyres	
Item number	19800476	
Valid tyre size	26 x 12.00 - 12	
LI / SI / PR	100 A8 / 113 A8, 8 PR	
TL/TT	TL	
Brand	Starco	
Tread pattern	AS Loader	



Notes and features

- The AS Loader was specially developed for skid steer loaders and compact tractors.
- Its tractor pattern provides high traction and excellent selfcleaning properties.
- The tyre performs excellently, even on soft and muddy surfaces.



Technical Informations

Item number	19800476
EAN	5707562380209
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	100 A8 / 113 A8, 8 PR
TL/TT	TL
Brand	Starco
Tread pattern	AS Loader
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,30
Recommended rim size	10.5
Maximum air pressure [bar].	2,10
Section width (mm)	318
Outer diameter of tyre [mm].	654
Stat. radius (SLR) [mm]	282
Rolling circumference [mm].	1954
Tread depth (mm)	15,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
100 A8	800	40	Drive Wheel	2,10	
113 A8	1150	40	Free Rolling	2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.