

TYRES

Product group	Tyres
Item number	19800485
Valid tyre size	520 / 50 - 17
LI / SI / PR	162 A8 / 159 B
TL/TT	TL
Brand	Starco
Tread pattern	AW



Notes and features

- The Starco AW is a versatile implement tyre for various agricultural trailers.
- It is distinguished by high reliability and a long service life.
- The tyre provides high load capacity at low inflation pressure.



Technical Informations

Item number	19800485
EAN	5707562336923
Valid tyre size	520 / 50 - 17
LI / SI / PR	162 A8 / 159 B
TL/TT	TL
Brand	Starco
Tread pattern	AW
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,50
Recommended rim size	16.00
Maximum air pressure [bar].	4,00
Section width (mm)	520
Outer diameter of tyre [mm].	970
Stat. radius (SLR) [mm]	425
Rolling circumference [mm].	2900
Tread depth (mm)	11,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		4,00	
159 B	4375	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.