

TYRES

Product group	Tyres	
Item number	19800550	
Valid tyre size	10 - 16.5	
LI / SI / PR	134 A2, 10 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	SG-810	



Notes and features

- The Deli SG-810 is a tyre for compact loaders, dumpers and telescopic loaders.
- The specially reinforced sidewall (Heavy Duty) provides very good protection against cuts and punctures and ensures a long service life.



Technical Informations

Item number	19800550
EAN	8994242018171
Valid tyre size	10 - 16.5
Alternative size 1	260/70-16.5
LI / SI / PR	134 A2, 10 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-810
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,86
Recommended rim size	8.25
Maximum air pressure [bar].	4,80
Section width (mm)	266
Outer diameter of tyre [mm].	790
Stat. radius (SLR) [mm]	353
Rolling circumference [mm].	2354
Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A2	2120	10		4,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.