

TYRES

Product group	Tyres	
Item number	19811070	
Valid tyre size	400 / 50 - 15	
LI / SI / PR	109 A8 / 121 A8, 10 PR	
TL/TT	TL	
Brand	Starco	
Tread pattern	AS Dumper II	



Notes and features

- The AS Dumper is an MPT bias tyre for dumpers, loaders and telescopic handlers.
- Its tractor pattern provides high traction and excellent selfcleaning properties.
- The durable rubber compound ensures a long service life for the tyre.
- Some dimensions are available in the AS Dumper II version with a reinforced casing construction.



Technical Informations

Item number	19811070
EAN	5707562363790
Valid tyre size	400 / 50 - 15
Alternative size 1	31x15.50-15
LI / SI / PR	109 A8 / 121 A8, 10 PR
TL/TT	TL
Brand	Starco
Tread pattern	AS Dumper II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,98
Recommended rim size	13.00
Maximum air pressure [bar].	3,00
Section width (mm)	380
Outer diameter of tyre [mm].	780
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2401
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40	Drive Wheel	3,00	LLV
121 A8	1450	40	Free Rolling	3,00	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.