

TYRES

Product group	Tyres
Item number	19811073
Valid tyre size	315 / 80 - 18
LI / SI / PR	136 A8 / 148 A8, 16 PR
TL/TT	TL
Brand	Starco
Tread pattern	AS Dumper



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The AS Dumper is an MPT bias tyre for dumpers, loaders and telescopic handlers.
- Its tractor pattern provides high traction and excellent self-cleaning properties.
- The durable rubber compound ensures a long service life for the tyre.
- Some dimensions are available in the AS Dumper II version with a reinforced casing construction.

Technical Informations

Item number	19811073
EAN	5707562146683
Valid tyre size	315 / 80 - 18
Alternative size 1	12.5/80-18
LI / SI / PR	136 A8 / 148 A8, 16 PR
TL/TT	TL
Brand	Starco
Tread pattern	AS Dumper
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,25
Recommended rim size	9.00
Permitted rim size	W9, 11
Maximum air pressure [bar].	4,90
Section width (mm)	314
Outer diameter of tyre [mm].	981
Stat. radius (SLR) [mm]	444
Rolling circumference [mm].	2839
Tread depth (mm)	26,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40	Drive Wheel	4,90	LLV
148 A8	3150	40	Free Rolling	4,90	LLV