

TYRES

Product group	Tyres
Item number	19812556
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	154 A6 / 150 A8, 16 PR
TL/TT	TL
Brand	MRL
Tread pattern	MIM 374



Notes and features

- The MRL MIM 374 is an agricultural tyre for tractors, which can also be used on backhoe loaders and agricultural trailers.
- Its curved lugs with wide spaces provide good traction, ride comfort, self-cleaning and a long service life.
- The especially wide lugs enable good ground contact for excellent traction on towing machines.

Technical Informations

Item number	19812556
EAN	8907375010448
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	154 A6 / 150 A8, 16 PR
TL/TT	TL
Brand	MRL
Tread pattern	MIM 374
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	41,45
Recommended rim size	W9
Permitted rim size	W9
Maximum air pressure [bar].	4,90
Section width (mm)	308
Outer diameter of tyre [mm].	965
Stat. radius (SLR) [mm]	444
Rolling circumference [mm].	2847
Tread depth (mm)	28,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	88
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A6	3750	30		4,90	LLV
150 A8	3350	40		4,90	LLV