Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	19812558
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MIM 374



Notes and features

- The MRL MIM 374 is an agricultural tyre for tractors, which can also be used on backhoe loaders and agricultural trailers.
- Its curved lugs with wide spaces provide good traction, ride comfort, self-cleaning and a long service life.
- The especially wide lugs enable good ground contact for excellent traction on towing machines.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19812558
EAN	8907375005581
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MIM 374
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,75
Recommended rim size	9
Permitted rim size	9
Maximum air pressure [bar].	4,10
Section width (mm)	290
Outer diameter of tyre [mm].	845
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2473
Tread depth (mm)	23,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	65
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A6	2180	30		4,10	LLV
131 A8	1950	40		4,10	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.