

TYRES

Product group	Tyres
Item number	19812585
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	MRL
Tread pattern	X POWER FLR 333



Notes and features

- The MRL X POWER FLR 333 was developed for agricultural trailers, tankers and spreaders.
- The tyre offers very high load capacities with low soil compaction at the same time.
- Its block tread pattern provides good rolling characteristics for low fuel consumption, good self-cleaning and ride comfort.

Technical Informations

Item number	19812585
EAN	8907375053117
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	MRL
Tread pattern	X POWER FLR 333
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	124,00
Recommended rim size	AG16
Maximum air pressure [bar].	5,00
Section width (mm)	543
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	549
Rolling circumference [mm].	3767
Tread depth (mm)	19,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		5,00	
162 E	4750	70		5,00	