

TYRES

Product group	Tyres
Item number	19812586
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	MRL
Tread pattern	S POWER FLR 335



Notes and features

- The MRL S POWER FLR 335 is a tyre for agricultural trailers, tankers and manure spreaders for field and road applications.
- In the field, the tyre provides good flotation characteristics for optimum soil protection.
- The special non-directional block tread pattern guarantees high mobility and traction on all kinds of soils.
- On road journeys, the tyre is characterised by high ride comfort.

Technical Informations

Item number	19812586
EAN	8907375053124
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	MRL
Tread pattern	S POWER FLR 335
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	126,00
Recommended rim size	AG16
Maximum air pressure [bar].	4,00
Section width (mm)	543
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	549
Rolling circumference [mm].	3767
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		4,00	
162 E	4750	70		4,00	