Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	19866031	
Valid tyre size	195 / 70 R 15 C	
LI / SI / PR	104 / 102 N	
TL/TT	TL	
Brand	GT Radial	
Tread pattern	KargoMax ST 6000	





Notes and features

- The Kargomax ST-6000 is a tyre for car trailers and caravans.
- This tyre is an optimum synthesis of traction, ride comfort and durability.
- The newly developed rubber compound ensures high mileage and low rolling resistance.
- The tyres are approved for trailer use only.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19866031
EAN	6932877115256
Valid tyre size	195 / 70 R 15 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	GT Radial
Tread pattern	KargoMax ST 6000
M+S	M+S
Rolling resistance	C
Wet grip	C
Rolling noise [db].	70
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	11,58
Recommended rim size	6
Maximum air pressure [bar].	4,50
Section width (mm)	201
Outer diameter of tyre [mm].	655
Stat. radius (SLR) [mm]	297
Rolling circumference [mm].	1998
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140		4,50	
102 N	850	140		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.