Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres
Item number	19866033
Valid tyre size	175 / 75 R 16 C
LI / SI / PR	101 / 99 R (104 N), 8 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Maxmiler Ex



Notes and features

- The GT Radial Maxmiler EX is an all-season tyre for light trucks, vans and car trailers.
- The tread pattern with overlapping lateral sipes and three circumferential grooves provides very good drainage and excellent grip on wet roads.
- The tread pattern blocks in the tread centre and sturdy tyre shoulders ensure stable cornering, good steering control and driving safety.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19866033
EAN	6932877194664
Valid tyre size	175 / 75 R 16 C
LI / SI / PR	101 / 99 R (104 N), 8 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Maxmiler Ex
M+S	M+S
Rolling resistance	D
Wet grip	C
Rolling noise [db].	70
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	10,80
Recommended rim size	5J
Permitted rim size	4.50J, 5.50J
Maximum air pressure [bar].	4,80
Section width (mm)	177
Outer diameter of tyre [mm].	668
Stat. radius (SLR) [mm]	315
Rolling circumference [mm].	2031
Tread depth (mm)	9,1
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
101 R	825	170	Single	4,80	
104 N	900	140	Single	4,80	
99 R	775	170	Twin	4,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.