Bohnenkamp Moving Professionals

18.11.2024

TYRES

Product group	Tyres
Item number	19912089
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	152 / 148 A7
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Boka Terra



Notes and features

- The Boka Terra is a hot retreaded tyre with a typical excavator tread pattern.
- The non-directional pattern provides good traction.
- The tyre guarantees high stability and is also ideally suited to road use.
- When used as twin wheels, the guard ring prevents foreign objects from penetrating the twin tyres.
- The tyres are perfectly protected against damages caused by the penetration of stones and other objects.
- The Boka Terra can be mounted on standard as well as reinforced EM rims.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19912089
EAN	4040658077050
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	152 / 148 A7
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Boka Terra
Type of retreading	Hot retreaded (bead-to-bead)
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	76.00
Recommended rim size	8.25
Maximum air pressure [bar].	8,00
Section width (mm)	302
Outer diameter of tyre [mm].	1043
Rolling circumference [mm].	3275
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A7	3550	35		8,00	
148 A7	3150	35		8,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.