

TYRES

| Product group | Tyres | |
|-----------------|------------|--|
| Item number | 19965200 | |
| Valid tyre size | 165 R 14 C | |
| LI / SI / PR | 97 / 95 R | |
| TL/TT | TL | |
| Brand | Nankang | |
| Tread pattern | CW-25 | |



Notes and features

 The Nankang CW-25 is a summer tyre for commercial vehicles and vans.



Technical Informations

| tt | 40005000 |
|------------------------------|---------------|
| Item number | 19965200 |
| EAN | 4040658020483 |
| Valid tyre size | 165 R 14 C |
| LI / SI / PR | 97 / 95 R |
| TL/TT | TL |
| Brand | Nankang |
| Tread pattern | CW-25 |
| Rolling resistance | С |
| Wet grip | С |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 8,80 |
| Recommended rim size | 4.50 |
| Permitted rim size | 4, 5 |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 166 |
| Outer diameter of tyre [mm]. | 623 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 97 R | 730 | 170 | Single | 4,50 | |
| 95 R | 690 | 170 | Twin | 4,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.