# Bohnenkamp Moving Professionals

#### 05.02.2025

### **TYRES**

Product group	Tyres	
Item number	19965365	
Valid tyre size	205 / 65 R 15 C	
LI / SI / PR	102 / 100 T	
TL/TT	TL	
Brand	Ovation	
Tread pattern	V-02	



#### Notes and features

- Dear trading partner, this item is not part of our main • programme. For this reason, we can only publish limited technical information in the online shop.
- For further information, please do not hesitate to contact . us by telephone
- Agricultural machinery business: +49 541 12163-100 •
- Tyre business: +49 541 12163-200

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

## **Technical Informations**

Item number	19965365
EAN	4040658062940
Valid tyre size	205 / 65 R 15 C
LI / SI / PR	102 / 100 T
TL/TT	TL
Brand	Ovation
Tread pattern	V-02
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	9,00
Recommended rim size	6
Permitted rim size	5.5, 6.5
Maximum air pressure [bar].	3,75
Section width (mm)	209
Outer diameter of tyre [mm].	647
Stat. radius (SLR) [mm]	297
Rolling circumference [mm].	1960
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 T	850	190	Single	3,75	
100 T	800	190	Twin	3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.