

TYRES

Product group	Tyres	
Item number	19966297	
Valid tyre size	6.00 - 16	
LI / SI / PR	102 / 98 K, 10 PR	
TL/TT	TT	
SET	Tube	
Brand	Boka Truck	
Tread pattern	Lug	





Notes and features

- The Boka Truck Lug is extremely resistant against damages.
- It is characterised by high mileage.
- It provides good traction on any kind of road.



Technical Informations

Item number	19966297
EAN	4040658073205
Valid tyre size	6.00 - 16
LI / SI / PR	102 / 98 K, 10 PR
TL/TT	тт
SET	Tube
Valve designation	TR 77 A
Brand	Boka Truck
Tread pattern	Lug
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	24,53
Recommended rim size	4.00E
Permitted rim size	4.50E
Maximum air pressure [bar].	5,30
Section width (mm)	160
Outer diameter of tyre [mm].	740
Tread depth (mm)	8,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 K	850	110	Single	5,30	
98 K	750	110	Twin	5,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.