

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 19966300           |
| Valid tyre size | 7.50 - 16          |
| LI / SI / PR    | 122 / 118 K, 14 PR |
| TL/TT           | TT                 |
| SET             | Tube + Flap        |
| Brand           | Boka Truck         |
| Tread pattern   | Rib                |



Bohnenkamp  
■ ■ ● Moving Professionals

**BOKA** TRUCK

## Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 19966300           |
| EAN                          | 4040658060779      |
| Valid tyre size              | 7.50 - 16          |
| LI / SI / PR                 | 122 / 118 K, 14 PR |
| TL/TT                        | TT                 |
| SET                          | Tube + Flap        |
| Valve designation            | TR 77 A            |
| Brand                        | Boka Truck         |
| Tread pattern                | Rib                |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 54             |
| Nettogewicht [kg] (gültig)   | 21,40              |
| Recommended rim size         | 5.50F              |
| Permitted rim size           | 6.00G              |
| Maximum air pressure [bar].  | 7,30               |
| Section width (mm)           | 220                |
| Outer diameter of tyre [mm]. | 808                |
| Tread depth (mm)             | 10,0               |
| E-Ready                      | No                 |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 122 K | 1500               | 110          | Single        | 7,30                     |              |
| 118 K | 1320               | 110          | Twin          | 7,30                     |              |