Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres	
Item number	19966301	
Valid tyre size	7.00 - 16	
LI / SI / PR	118 / 114 K, 14 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	Boka Truck	
Tread pattern	Rib	



Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.

Bohnenkamp Moving Professionals

Technical Informations

Item number19966301EAN4040658068010Valid tyre size7.00 - 16Ll / SI / PR118 / 114 K, 14 PRTL/TTTTSETTube + FlapValve designationTR 75 ABrandBoka TruckTread patternRibAntistaticNo
Valid tyre size7.00 - 16LI / SI / PR118 / 114 K, 14 PRTL/TTTTSETTube + FlapValve designationTR 75 ABrandBoka TruckTread patternRib
LI / SI / PR 118 / 114 K, 14 PR TL/TT TT SET Tube + Flap Valve designation TR 75 A Brand Boka Truck Tread pattern Rib
TL/TT TT SET Tube + Flap Valve designation TR 75 A Brand Boka Truck Tread pattern Rib
SET Tube + Flap Valve designation TR 75 A Brand Boka Truck Tread pattern Rib
Valve designation TR 75 A Brand Boka Truck Tread pattern Rib
Brand Boka Truck Tread pattern Rib
Tread pattern Rib
Antistatic No
Tyre colour Black
ECE regulation number ECE 54
Nettogewicht [kg] (gültig) 19,70
Recommended rim size 5.50F
Permitted rim size 6.00G
Maximum air pressure [bar]. 7,30
Section width (mm) 200
Outer diameter of tyre [mm]. 775
Stat. radius (SLR) [mm] 369
Tread depth (mm) 8,0
E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 K	1320	110	Single	7,30	
114 K	1180	110	Twin	7,30	

14.11.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.