

TYRES

Product group	Tyres	
Item number	19966303	
Valid tyre size	8.25 - 16	
LI / SI / PR	126 / 122 K, 14 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	Boka Truck	
Tread pattern	Rib	





Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.



Technical Informations

Item number	19966303
EAN	4040658060786
Valid tyre size	8.25 - 16
LI / SI / PR	126 / 122 K, 14 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	TR 77 A
Brand	Boka Truck
Tread pattern	Rib
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	26,63
Recommended rim size	6.50H
Permitted rim size	6.00G
Maximum air pressure [bar].	6,30
Section width (mm)	237
Outer diameter of tyre [mm].	856
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 K	1700	110	Single	6,30	
122 K	1500	110	Twin	6,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.