Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19966306	
Valid tyre size	7.50 - 20	
LI / SI / PR	130 / 126 G, 14 PR	
TL/TT	TT	
SET	Tube + Flap	
Brand	Boka Truck	
Tread pattern	Rib	



Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.

Bohnenkamp Moving Professionals

Technical Informations

Item number 1	19966306
	13200200
EAN 4	4040658060793
Valid tyre size	7.50 - 20
LI / SI / PR	130 / 126 G, 14 PR
TL/TT	Π
SET 1	Tube + Flap
Valve designation	TR 175 A
Brand E	Boka Truck
Tread pattern	Rib
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	29,00
Recommended rim size	6.00
Permitted rim size	6.00T, 6.50
Maximum air pressure [bar].	8,10
Section width (mm)	190
Outer diameter of tyre [mm].	910
Stat. radius (SLR) [mm]	210
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 G	1900	90	Single	8,10	
126 G	1700	90	Twin	7,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.