

TYRES

Product group	Tyres	
Item number	19966313	
Valid tyre size	10.00 - 20	
LI / SI / PR	146 / 142 G, 16 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	Boka Truck	
Tread pattern	Lug	





Notes and features

- The Boka Truck Lug is extremely resistant against damages.
- It is characterised by high mileage.
- It provides good traction on any kind of road.



Technical Informations

Item number	19966313
EAN	4040658062391
Valid tyre size	10.00 - 20
LI / SI / PR	146 / 142 G, 16 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Boka Truck
Tread pattern	Lug
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	46,24
Recommended rim size	7.50
Permitted rim size	7.5, 8.0
Maximum air pressure [bar].	8,10
Section width (mm)	278
Outer diameter of tyre [mm].	1054
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 G	3000	90	Single	8,10	
142 G	2650	90	Twin	7,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.