

TYRES

Product group	Tyres
Item number	19966314
Valid tyre size	10.00 - 20
LI / SI / PR	146 / 142 G, 16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Boka Truck
Tread pattern	Rib



Bohnenkamp
■ ■ ● Moving Professionals

BOKA TRUCK

Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.

Technical Informations

Item number	19966314
EAN	4040658061141
Valid tyre size	10.00 - 20
LI / SI / PR	146 / 142 G, 16 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Boka Truck
Tread pattern	Rib
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	46,24
Recommended rim size	7.50
Permitted rim size	7.5, 8.0
Maximum air pressure [bar].	8,10
Section width (mm)	278
Outer diameter of tyre [mm].	1062
Rolling circumference [mm].	3314
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 G	3000	90	Single	8,10	
142 G	2650	90	Twin	7,40	