

TYRES

| | |
|-----------------|--------------------|
| Product group | Tyres |
| Item number | 19966315 |
| Valid tyre size | 11.00 - 20 |
| LI / SI / PR | 149 / 145 G, 16 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Brand | Boka Truck |
| Tread pattern | Lug |



BOKA TRUCK

Notes and features

- The Boka Truck Lug is extremely resistant against damages.
- It is characterised by high mileage.
- It provides good traction on any kind of road.

Technical Informations

| | |
|------------------------------|--------------------|
| Item number | 19966315 |
| EAN | 4040658062384 |
| Valid tyre size | 11.00 - 20 |
| LI / SI / PR | 149 / 145 G, 16 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Valve designation | TR 175 A |
| Brand | Boka Truck |
| Tread pattern | Lug |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 51,51 |
| Recommended rim size | 8.00 |
| Permitted rim size | 8.0, 8.5 |
| Maximum air pressure [bar]. | 8,10 |
| Section width (mm) | 316 |
| Outer diameter of tyre [mm]. | 1128 |
| Tread depth (mm) | 16,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 149 G | 3250 | 90 | Single | 8,10 | |
| 145 G | 2900 | 90 | Twin | 7,40 | |