

TYRES

Product group	Tyres
Item number	19966316
Valid tyre size	11.00 - 20
LI / SI / PR	149 / 145 G, 16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Boka Truck
Tread pattern	Rib



Bohnenkamp
■ ■ ● Moving Professionals

BOKA TRUCK

Notes and features

- The Boka Truck is a bias tyre with proven grooved tread pattern.
- It is characterised by its compact tread pattern with continuous shoulder line.

Technical Informations

Item number	19966316
EAN	4040658061158
Valid tyre size	11.00 - 20
LI / SI / PR	149 / 145 G, 16 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Boka Truck
Tread pattern	Rib
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	51,51
Recommended rim size	8.00
Permitted rim size	8.0, 8.5
Maximum air pressure [bar].	8,10
Section width (mm)	291
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	517
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 G	3250	90	Single	8,10	
145 G	2900	90	Twin	7,40	