Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	19966317	
Valid tyre size	12.00 - 20	
LI / SI / PR	154 / 149 G, 18 PR	
TL/TT	TT	
SET	Tube + Flap	
Brand	Boka Truck	
Tread pattern	Lug	



Notes and features

- The Boka Truck Lug is extremely resistant against damages.
- It is characterised by high mileage.
- It provides good traction on any kind of road.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19966317
EAN	4040658062353
Valid tyre size	12.00 - 20
LI / SI / PR	154 / 149 G, 18 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Boka Truck
Tread pattern	Lug
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	58,85
Recommended rim size	8.5
Permitted rim size	8.50, 9.0
Maximum air pressure [bar].	8,10
Section width (mm)	340
Outer diameter of tyre [mm].	1170
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 G	3750	90	Single	8,10	
149 G	3250	90	Twin	7,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.