

TYRES

Product group	Tyres	
Item number	19968062	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	152 / 148 M	
TL/TT	TL	
Brand	Bohnenkamp	
Tread pattern	RE Power WP Alltrac	



Notes and features

- The RE Power WP Alltrac is a versatile, remoulded tyre on a Windpower casing.
- Its universal tread pattern offers a variety of applications in regional transport.
- Its tread pattern provides low heat generation thanks to its special shoulder design.
- The Alltrac offers very high mileage and even wear.
- The tyre is marked with alpine symbol.



Technical Informations

Item number	19968062
EAN	4040658077111
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	152 / 148 M
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	RE Power WP Alltrac
M+S	M+S
3PMSF	3PMSF
Type of retreading	Hot retreaded (tread)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 109
Nettogewicht [kg] (gültig)	71,00
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	314
Outer diameter of tyre [mm].	1028
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130		9,00	
148 M	3150	130		9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.