

TYRES

Product group	Tyres
Item number	19968064
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 M
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	RE Power WP Alltrac



Notes and features

- The RE Power WP Alltrac is a versatile, remoulded tyre on a Windpower casing.
- Its universal tread pattern offers a variety of applications in regional transport.
- Its tread pattern provides low heat generation thanks to its special shoulder design.
- The Alltrac offers very high mileage and even wear.
- The tyre is marked with alpine symbol.

Technical Informations

Item number	19968064
EAN	4040658077128
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 M
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	RE Power WP Alltrac
M+S	M+S
3PMSF	3PMSF
Type of retreading	Hot retreaded (tread)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 109
Nettogewicht [kg] (gültig)	71,00
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,50
Section width (mm)	314
Outer diameter of tyre [mm].	1092
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 M	4000	130		8,50	
150 M	3350	130		8,50	