

TYRES

Product group	Tyres
Item number	19968077
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	152 / 148 A7
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Boka Terra



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Boka Terra is a hot retreaded tyre with a typical excavator tread pattern.
- The non-directional pattern provides good traction.
- The tyre guarantees high stability and is also ideally suited to road use.
- When used as twin wheels, the guard ring prevents foreign objects from penetrating the twin tyres.
- The tyres are perfectly protected against damages caused by the penetration of stones and other objects.
- The Boka Terra can be mounted on standard as well as reinforced EM rims.

Technical Informations

Item number	19968077
EAN	4040658094743
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	152 / 148 A7
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Boka Terra
Type of retreading	Hot retreaded (bead-to-bead)
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	84,00
Recommended rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	302
Outer diameter of tyre [mm].	1100
Rolling circumference [mm].	3445
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A7	3550	35		9,00	
147 A7	3075	35		9,00	