

TYRES

Product group	Tyres
Item number	19981685
Valid tyre size	9.00 - 20
LI / SI / PR	140 B, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	Boka Terra
Tread pattern	SKL800



Bohnenkamp
■ ■ ● Moving Professionals

BOKA TERRA
LINE □ □ ○

Notes and features

- The SKL 800 is a robust tyre for use on wheeled excavators.
- Its classic open tread pattern offers good traction and self-cleaning properties.

Technical Informations

Item number	19981685
EAN	4040658061165
Valid tyre size	9.00 - 20
LI / SI / PR	140 B, 14 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Boka Terra
Tread pattern	SKL800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	47,00
Recommended rim size	7.0
Permitted rim size	7.00T, 7.5, 7.50V
Maximum air pressure [bar].	7,00
Section width (mm)	260
Outer diameter of tyre [mm].	1030
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 B	2500	50		7,00	