

TYRES

Product group	Tyres
Item number	19981687
Valid tyre size	10.00 - 20
LI / SI / PR	148 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Boka Terra
Tread pattern	SKL800



Bohnenkamp
■ ■ ● Moving Professionals

BOKA TERRA

Notes and features

- The SKL 800 is a robust tyre for use on wheeled excavators.
- Its classic open tread pattern offers good traction and self-cleaning properties.

Technical Informations

Item number	19981687
EAN	4040658073212
Valid tyre size	10.00 - 20
LI / SI / PR	148 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 78 A
Brand	Boka Terra
Tread pattern	SKL800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	53,00
Recommended rim size	7.5
Permitted rim size	7.50V, 8.0, 8.00V
Maximum air pressure [bar].	7,50
Section width (mm)	280
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3180
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 B	3150	50		7,50	