

TYRES

Product group	Tyres
Item number	19981688
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Boka Terra
Tread pattern	SKL800



Bohnenkamp
■ ■ ● Moving Professionals

BOKA TERRA

Notes and features

- The SKL 800 is a robust tyre for use on wheeled excavators.
- Its classic open tread pattern offers good traction and self-cleaning properties.

Technical Informations

Item number	19981688
EAN	4040658061172
Valid tyre size	10.00 - 20
LI / SI / PR	146 B, 16 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 78 A
Brand	Boka Terra
Tread pattern	SKL800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	52,00
Recommended rim size	7.5
Permitted rim size	7.50V, 8.0, 8.00V
Maximum air pressure [bar].	8,10
Section width (mm)	280
Outer diameter of tyre [mm].	1062
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 B	3000	50		8,10	
	3750	25		8,10	