

TYRES

Product group	Tyres	
Item number	19995235	
Valid tyre size	205 / 65 R 17.5	
LI / SI / PR	129 / 127 K (132 / 132 G)	
TL/TT	TL	
Brand	Goodyear	
Tread pattern	KMAX T	



Notes and features

- The Goodyear KMAX T is a truck trailer tyre for longdistance and regional transport.
- Its strong casing and the low-wear tread pattern design guarantee high mileage.
- The tyre is protected against the penetration of small stones into the tread grooves, thus avoiding crack damages.
- Thanks to the rib edge blading, the tyre provides excellent braking performance on wet roads.



Technical Informations

Item number	19995235
EAN	5452000738059
Valid tyre size	205 / 65 R 17.5
LI / SI / PR	129 / 127 K (132 / 132 G)
TL/TT	TL
Brand	Goodyear
Tread pattern	KMAX T
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	С
Wet grip	В
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	24,50
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	213
Outer diameter of tyre [mm].	716
Stat. radius (SLR) [mm]	334
Rolling circumference [mm].	2199
Tread depth (mm)	11,2

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 K	1850	110	Single	9,00	
132 G	2000	90	Single	9,00	
127 K	1750	110	Twin	9,00	
132 G	2000	90	Twin	9,00	