

## **TYRES**

Product group	Tyres
Item number	19999911
Valid tyre size	IF 380 / 90 R 46
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363
Sonderpostenkategorie	DOT
type of damage	DOT





## **Notes and features**

- The Alliance 363 is an IF row crop tyre for heavy, selfpropelled field sprayers and tractors.
- It offers up to 20% higher load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The directional tread pattern design, divided in separate blocks, enables good grip on soft surfaces.
- The increased number of lugs and block distribution on the tread pattern ensure good ride comfort and low rolling resistance on roads.
- Its large contact area provides high traction, reduced fuel consumption and low soil compaction.
- The steel belted casing enables uniform ground pressure distribution and protection against damages, thus ensuring a long service life.



## **Technical Informations**

Item number	19999911
EAN	4040658088162
Valid tyre size	IF 380 / 90 R 46
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	157,26
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,40
Section width (mm)	389
Outer diameter of tyre [mm].	1842
Stat. radius (SLR) [mm]	853
Rolling circumference [mm].	5592
Tread depth (mm)	39,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 S	5600	65		4,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.