

RIMS

Product group	Rims
Item number	30012127
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	E2
Brand	Gianetti FAD

Technical Informations

Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	20,30
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Sapphire grey
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No