

RIMS

Product group	Rims
Item number	30060020
Valid rim size	6.5 - 15
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+124
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	2300
Speed Rims 1 [km/h]	105
Maximum speed [km/h].	105
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	25,40
Hump	kein Hump
Single / multi-part	mehrteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	Internal Valve
Preassembled valve	No