Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	30060040
Valid rim size	6.5 - 15
Rim connection	10/176/225
Bolt hole design	B3
Offset (mm)	+124
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Brand	Jantsa





Technical Informations

Load capacity of rim 1 [kg]	2650
Speed Rims 1 [km/h]	105
Maximum speed [km/h].	105
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	29,60
Hump	kein Hump
Single / multi-part	mehrteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Preassembled valve	No