Bohnenkamp Moving Professionals

10.11.2024

RIMS

Product group	Rims
Item number	30060041
Valid rim size	6.5 - 15
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-30
Rim colour	Silver
Brand	Jantsa





Load capacity of rim 1 [kg] 2300 Speed Rims 1 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Towed axle Nettogewicht [kg] (gültig) 28,50 Hump kein Hump Single / multi-part mehrteilig **Rim material** steel RAL RAL9006 **Cavity Sealed** No Verschweißung beidseitig No

Technical Informations

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No