

RIMS

Product group	Rims
Item number	30655027
Valid rim size	3.00 D - 8
Rim connection	5/82/130
Bolt hole design	FF1
Offset (mm)	-10
Rim colour	Silver
Brand	Mefro



Technical Informations	
Load capacity of rim 1 [kg]	850
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	3,00
Hump	kein Hump
Single / multi-part	geteilt
Quantity multi-piece	two-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim design industry	Standard
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	82
Bolt hole circle diameter [mm]	130
Valve seat	External Valve
Preassembled valve	No