

RIMS

Product group	Rims
Item number	30695185
Valid rim size	7.00 A x 8 H2
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Brand	Vlukon





Technical Informations		
Load capacity of rim 1 [kg]	425	
Speed Rims 1 [km/h]	100	
Maximum speed [km/h].	100	
Type of drive	Towed axle	
Nettogewicht [kg] (gültig)	2,95	
Hump	H2	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	
Verschweißung beidseitig	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.5
Preassembled valve	No