

## **RIMS**

Product group	Rims
Item number	30810276
Valid rim size	7.00 x 12
Rim connection	5/94/140
Bolt hole design	E1
Rim colour	White
Brand	Accuride





## **Technical Informations**

Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	750
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	80
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	8,20
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9016

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No