

RIMS

Product group	Rims
Item number	30810332
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-60
Rim colour	Silver
Brand	Accuride



Allgemeine Produktabbildung. Artikel kann abweichen



Technical Informations

Load capacity of rim 1 [kg]	3550
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3075
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	30,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No