

## RIMS

Product group	Rims
Item number	30812621
Valid rim size	AG 16.00 x 22.5 TH2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-95
Rim colour	Silver
Brand	Accuride



## Technical Informations

Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3550
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	51,00
Hump	TH2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	6
<b>Bolt hole diameter [mm]</b>	21.5
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R16
<b>hub hole diameter [mm].</b>	161
<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No