

RIMS

| | |
|------------------|----------------|
| Product group | Rims |
| Item number | 30855002 |
| Valid rim size | 6.00 I x 10 H2 |
| Rim connection | 5/94/140 |
| Bolt hole design | G1 |
| Offset (mm) | -4 |
| Rim colour | Silver |
| Brand | Mefro |



mefro wheels **M**

Technical Informations

| | |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 750 |
| Speed Rims 1 [km/h] | 140 |
| Maximum speed [km/h]. | 140 |
| Type of drive | Towed axle |
| Nettogewicht [kg] (gültig) | 5,50 |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |

| | |
|--------------------------------|----------------|
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |